

SAFETY DATA SHEET

According to Work Health and Safety Regulations 2011 and National Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals

Version 1.0

Printing date: 16/12/2016
Revision date: 16/12/2016

SDS Record Number: CSSS-TCO-010-XXXXX

1. Identification of the material and supplier

Material name: Tulux T700 15W-40 (CK-4) Diesel Engine Oil

Other means of identification: -

Recommended use: Can be used in diesel engine for lubricating, cooling and airproofing etc.

Restrictions on use:

Manufacturer:

Australia Supplier (Manufacturer): International Lubricant Distributors Pty. Ltd.

Address: Suite 11, 100 Hay Street Subiaco WA 6008 Australia

Contact person(E-mail): Telephone: -

Fax: +61 8 9381 1788 Emergency number: 1300 558 939

Other Information

New Zealand Supplier(Manufacturer): Waitomo Lubricants Limited (GST 104255744)

Address: 15 Ellis Street, Frankton, Hamilton, PO Box 5125, Hamilton 3242

Telephone: +64 7 847 0829 **Fax:** +64 7 846 0032

Emergency number: +64 7 847 0829 (24 Hrs)

New Zealand Supplier(Manufacturer): MTS ENERGY LTD

Address: 44 Northcote Road, North Shore, Auckland 0627, New Zealand

Telephone: +64 9 480 8921 **Fax:** +64 9 480 8398

Emergency number: 0800 399 993 (24 Hrs)

2. Hazards identification

Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

New Zealand:

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements:

Hazard Pictograms: No hazard pictogram is used.

Signal word: No signal word is used.

Hazard statement: Not applicable.

Precautionary statement:

Material name: Tulux T700 15W-40 (API CK-4) Diesel Engine Oil

Version #: 1.0

Printing date: 16-12-2016.

Revision date: 16-12-2016.

SDS Australia&New Zealand

1 / 8



Prevention: Not applicable. Response: Not applicable. Not applicable. Storage: Disposal: Not applicable. Other hazards which do not result in Not applicable.

classification:

3. Composition/information on ingredients			
Components	CAS No.	Percent	

Base oil 64742-55-8 70-90% Additive Mixture <20%

4. First aid measures

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in

the air, move the exposed person to fresh air. Get medical attention if coughing or

respiratory discomfort occurs.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if

contaminated. To remove the material from skin, use soap and water. Discard

contaminated clothing and shoes or thoroughly clean before reuse.

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if

worn, and flush eyes with water.

No specific first aid measures are required. Do not induce vomiting. As a precaution, get Ingestion:

medical advice.

Not available. Symptoms caused by exposure:

Medical Attention and Special Treatment: Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Extinguishing media which must not be

used for safety reasons:

Water.

Specific hazards arising from the

chemical:

In case of heat, fire and strong oxidants can lead to burning. Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides, phosphate, certain metal oxides and

other decomposition products, in the case of incomplete combustion.

Special protective equipment and precautions for fire fighters:

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location.

This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Personal Avoid build up of vapour. Ensure sufficient supply of air. Avoid contact with eyes or skin. precautions, protective equipment and emergency procedures:

Contact with water - danger of sliding. Wear appropriate personal protective equipment and clothing to prevent exposure. Increase ventilation. Evacuate all unprotected

2/8

personnel.

Environmental precautions: If leakage occurs, dam up. Prevent surface and ground-water infiltration, as well as ground

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil SDS Australia&New Zealand Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016.



penetration. Prevent from entering drainage system. If accidental entry into drainage

system occurs, inform responsible authorities.

Methods and materials for containment

and cleaning up:

For large spills: Remove with vacuum truck or pump to storage/salvage vessels.

For small spills: Soak up residue with an absorbent such as clay, sand or other suitable

material. Place in non-leaking container and seal tightly for proper disposal.

7. Handling and storage

Precautions for safe handling:

Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Electrostatic discharge may be generated during pumping - this may result in fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Conditions for safe storage, including any

incompatibilities:

Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Storage regulation

ignition.

8. Exposure controls/personal protection

Control parameters - exposure

standards, biological monitoring:

Exposure Levels

Occupational exposure limits:

Not available

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)			
Components	Туре	Value	Form
Not available.	Not available.	Not available.	Not available.
Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)			
Components	Туре	Value	Form
Not available.	Not available.	Not available.	Not available.

No exposure standards have been established for this material, however, the TWA National occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m3, the STEL National occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 10 mg/m3.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Appropriate engineering controls:

Provide sufficient ventilation to keep airborne levels as low as possible. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a

local exhaust ventilation system is required.

Personal protective equipment:

Eye/face protection: No special eye protection is normally required. Where splashing is possible, wear safety

glasses with side shields as a good safety practice.

Skin protection: No special protective clothing is normally required. Where splashing is possible, select

protective clothing depending on operations conducted physical requirements and other

substances in the workplace.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil

Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016. SDS Australia&New Zealand

3 / 8



practices, precautions should be taken to avoid breathing of material...If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

Hand protection: Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Form: Oily liquid

Color: Transparent, brown

Odor: Odorless or slight odor

Odour threshold:Not availablePH:Not availableMelting point/Freezing point:Not availableBoiling point and boiling range:Not available

Flash point: 233 °C (Open Cup)(typical)

Evaporation rate:

Flammability (solid, gas):

Upper/lower flammability or explosive

Not available

Not available

limits:

Vapor pressure:Not availableVapor density:Not available

Density: 0.80kg/L~0.90kg/L (20°C)

Solubility (H_2O): Insoluble in water. Partition coefficient (n-octanol/water): > 6 (estimated value)

Auto-ignition temperature: >260°C

Decomposition temperature: Not available

Viscosity, dynamic: $12.5 \text{mm}^2/\text{s} - 16.3 \text{ mm}^2/\text{s} (100 ^\circ\text{C})$

Specific heat value:

Particle size:

Volatile organic compounds content:

Not available

Not available

Not available

Saturated vapour concentration:

Release of invisible flammable vapours

Not available

and gases:

Additional parameters

Shape and aspect ratio:

Crystallinity:

Not available

Dustiness:

Not available

Surface area:

Not available

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016.



Biodurability or biopersistence: Not available

10. Stability and reactivity

Reactivity: Stable under recommended transport or storage conditions.

Chemical stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions: Contact with strong oxidants.

Conditions to avoid: Incompatible materials. Avoid extreme temperatures, sun exposure, and the fire source.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides, phosphate,

certain metal oxides and other decomposition products, in the case of incomplete

combustion.

11. Toxicological information

Toxicological data:

Acute toxicity:

LD50(Oral, Rat): >5g/kg LD50(Dermal, Rabbit): >5g/kg LC50(Inhalation, Rat): >10g/m³

Base oil (CAS: 64742-55-8)

> 5000 mg/kg bw LD50(Oral, Rat): LD50(Dermal, Rabbit): > 2000 mg/kg bw LC50(Inhalation, Rat): 2.18 mg/L air Skin corrosion/Irritation: No data available. Serious eye damage/irritation: No data available. Respiratory or skin sensitization: No data available. Germ cell mutagenicity: No data available. Carcinogenicity: No data available. Reproductive toxicity: No data available. STOT- single exposure: No data available. STOT-repeated exposure: No data available. Aspiration hazard: No data available.

Other information This product has no known adverse effect on human health.

Information on routes of exposure No data available. Symptoms related to exposure No data available. No data available. **Numerical measures of toxicity** No data available. Immediate, delayed and chronic health

effects from exposure

12. Ecological information

Ecotoxicity:

Acute t	oxicity	Time	Species	Method	Evaluation	Remarks
LC50	N/A	96h	Fish	OECD 203	N/A	N/A
EC50	N/A	48h	Daphnia	OECD 202	N/A	N/A
EC50	N/A	72h	Algae	OECD 201	N/A	N/A

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil SDS Australia&New Zealand Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016.



Persistence and degradability:

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

This material is not expected to be readily biodegradable.

This material contains components with potential to bioaccumulation.

If into the soil, this material will be adsorbed and not flow.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Safe handling and disposal methods: Disposal of any contaminated packaging: Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Australia:

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

New Zealand:

Product Disposal

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Australia:

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

New Zealand:

Not classified as Dangerous Goods for transport according to the NZS 5433:2012 Transport of Dangerous Goods on Land.

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil

Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016. SDS Australia&New Zealand

6 / 8



Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

U.N. Number

None Allocated

Proper Shipping Name

None Allocated

DG Class

None Allocated

Packing Group

None Allocated

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

New Zealand:

Not classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Australia HVIC: Listed substance

Not available.

New Zealand Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply	Quantity beyond which controls apply
	for closed containers	when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

New Zealand Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

• •	* * * * * * * * * * * * * * * * * * * *	
Inventory status:		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Not available.
Canada	Domestic Substances List (DSL)	Not available.
Canada	Non-Domestic Substances List (NDSL)	Not available.
China	Inventory of Existing Chemical Substances in China	Not available.
	(IECSC)	
Europe	European Inventory of Existing Commercial Chemical	Not available.
	Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	Not available.
Japan	Inventory of Existing and New Chemical Substances	Not available.
	(ENCS)	
Korea	Existing Chemicals List (ECL)	Not available.
New Zealand	New Zealand Inventory	Not available.

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016.



Philippines Philippine Inventory of Chemicals and Chemical Not available.

Substances (PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Not available.

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Indication of changes: Version 1.0

Date of preparation or review: 2016.12.16

Key abbreviations or acronyms CAS: Chemical Abstracts Service

used: LC50: Lethal Concentration 50

EC50: Concentration for 50% of maximal effect

LD50: Lethal dose 50%

MAC: maximum allowable concentration, MAC)

PC-TWA: permissible concentration-time weighted average PC-STEL: permissible concentration-short term exposure limit

reference Australia:

Standard for the Uniform Scheduling of Medicines and Poisons.

Approved criteria for classifying hazardous substances [NOHSC: 1008(2004)].

National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:

2011(2003)].

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted

carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH)

New Zealand:

Workplace Exposure Standards and Biological Exposure Indices

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO

CoP 8-1 0906).

Assigning a hazardous substance to a group standard.

American Conference of IndustriaLHygienists (ACGIH)

Material name: Tulux T700 15W-40 (API CK -4) Diesel Engine Oil

Version #: 1.0 Printing date: 16-12-2016. Revision date: 16-12-2016.

SDS Australia&New Zealand
8 / 8