

| | |
|---------|---|
| Product | Sinopec TO-4 Heavy Duty Classic Transmission Fluid |
| Summary | Product description Sinopec TO-4 Heavy Duty Classic Transmission Fluid is a range of products formulated with high-quality mineral oils and an advanced additive system. Improvements in the performance of heavy-duty equipment have been made possible by advances in technology and improved power-train designs, which in turn require higher performing fluids. Sinopec TO-4 Heavy Duty Classic Transmission Fluid grades are specially designed to meet the demanding Caterpillar TO-4 specification. |

Applications

Sinopec TO-4 Heavy Duty Classic Transmission Fluid is suitable for use in:

- Heavy-duty transmissions, gearboxes, final drives and hydraulic systems used in off-highway applications, where a Caterpillar TO-4 product is recommended.
- Other heavy-duty applications in the mining, construction, quarrying and agricultural industries.
- Manual, power-shift and automatic transmissions where Allison C-4 fluids (SAE 10W and 30 grades) are recommended.
- Mobile hydraulic equipment applications.
- Applications where paper and elastomer disc materials are used, and advanced frictional properties are required to extend clutch life and provide slippage control under severe heavy-load conditions.
- For more demanding or critical applications, for example where a ZF approved product is required, consider using the product Sinopec TO-4 Heavy Duty Transmission Fluid, which has a higher specification.

Features and benefits

- Good antiwear properties and load carrying ability reduce gear wear and extend the life of heavy-duty transmission systems, gearboxes and final drives, leading to improved performance and reduced equipment downtime.
- Outstanding oxidation stability, thermal stability and detergency prevent the build up of deposits and ensure long fluid life.
- Advanced frictional properties provide the clutch friction retention and slippage control required in equipment that uses modern paper or elastomer disc materials.
- Compatible with modern clutch materials and elastomers, to extend component life and prevent oil leakage.
- Effective control of foaming together with good air-release properties ensure smooth transfer of power and shifting performance, and reduce fluid loss in severe service conditions.
- Very good low-temperature properties protect against wear under cold start up and running conditions.

Typical data

| Sinopec TO-4 Heavy Duty Classic Transmission Fluid | | | | |
|---|--------|--------|--------|-------|
| SAE viscosity grade | 10W | 30 | 50 | 60 |
| Kinematic viscosity, ASTM D 445 | | | | |
| cSt @ 40°C | 47.1 | 99.2 | 229.1 | 310.4 |
| cSt @ 100°C | 7.0 | 11.3 | 19.4 | 23.8 |
| Viscosity, Brookfield, ASTM D 2983 | | | | |
| cP @ -15°C | – | – | 41,000 | – |
| cP @ -25°C | – | 60,000 | – | – |
| cP @ -35°C | 37,000 | – | – | – |
| Viscosity index, ASTM D 2270 | 106 | 100 | 96 | 96 |
| FZG gear scuffing, load stage, ASTM D 5182 | 12 | 12 | 12 | 12 |
| Pour point, °C, ASTM D 97 | -39 | -27 | -21 | -9 |
| Flash point (COC), °C, ASTM D 92 | 230 | 240 | 250 | 270 |

These data are given as an indication of typical values and not as exact specifications.

Industry and OEM specifications

| Sinopec TO-4 Heavy Duty Classic Transmission Fluid meets the performance requirements of the following industry specifications: | |
|--|------------------|
| Sinopec | Q/SH303 533-2009 |

| Sinopec TO-4 Heavy Duty Classic Transmission Fluid meets the performance requirements of the following OEM specifications: | |
|---|--|
| Allison | C-4 (SAE 10W and 30) |
| Caterpillar | TO-4 |
| Komatsu | KES 07.868.1 (SAE 30) |
| ZF | TE-ML 03C (SAE 30) TE-ML 07F (SAE 30) |

Accuracy of information

Data provided in this PDS is typical and subject to change as a result of continuing product research and development. The information given was correct at the time of printing. The typical values given are subject to variations in the testing procedures and the manufacturing process may also result in slight variations. Sinopec guarantees that its lubricants meet any industry and OEM specifications referred to on this data sheet.

Sinopec cannot be held responsible for any deterioration in the product due to incorrect storage or handling. Information on best practice is available from your local distributor.

Product and environmental safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Material Safety Data Sheet (MSDS) is followed. Please consult the MSDS for more detailed advice on handling; MSDSs are available from your local distributor. Do not use the product in applications other than those suggested.

As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The SINOPEC trademark is registered and protected in Australia.

Issued: September 2012

© Sinopec 2012

77-TO-4-Heavy-Duty-Classic-Transmission-Fluid