

## PRODUCT DATA SHEET



# ILD CHAIN & BAR OIL; ISO 100,150,220,320

### DESCRIPTION

ILD Chain & Bar Oils are high quality chain and bar lubricants intended to provide cost effective lubrication of chains, sprockets and guide bars of chain saws with either automatic or hand oilers.

### APPLICATIONS

Recommended for the lubrication of chainbars and sprockets of all types of chainsaws using either hand-operated or automatic oilers, including for use under severe conditions.

### PRODUCT BENEFITS

Reduces wear:  
Reduces wear on the chain bar and sprockets.

Less waste:  
The tackiness quality of the product reduces sling-off from the chain.

### PACKAGING

1000 Ltr IBC's, 205 Ltr drums, 20 Ltr drums.

### TYPICAL CHARACTERISTICS

	ISO 100	ISO 150	ISO 220	ISO 320
Appearance	Light Amber to Brown			
Density @ 15°C kg/L	0.856	0.866	0.877	0.885
Viscosity, cSt at 40° C	100	150	220	320
Viscosity, cSt at 100° C	11.4	15	19.5	23.8
Flash point °C	>215	>220	>220	>220
Pour point °C	-8	-8	-10	-10

---

These characteristics are typical values and do not represent a specification.

---