

ILD ATF MULTI FUNCTION

PREMIUM MINERAL TRANSMISSION FLUID

DESCRIPTION & APPLICATION:

ILD ATF Multi Function Fluid uses premium mineral base oils combined with top quality additives formulated for auto transmissions and power steering applications.

ILD ATF Multi Function Fluid is designed for use in passenger cars, 4WD and light commercial vehicles where GM Dexron III®, Ford Mercon® and BTR 95LE / 85LE fluids have been specified, it has improved low temperature properties and excellent smooth shift operation, at cold start and normal driving conditions, it is also suitable for Hydrostatic transmissions and Hydraulic systems.

BENEFITS:

- High thermal stability
- Improved power transfer and fuel economy.
- Low pour point / No foaming

TYPICAL CHARACTERISTICS*:

TEST	TYPICAL VALUE
Density 15° C g/cm ³	0.855
Viscosity 40°C cSt	36.4
Viscosity 100°C cSt	7.2
Viscosity Index	164
Flash Point °C	>210
Colour	Red

PRODUCT SIZES

PRODUCT CODE	PACK SIZE	CTN QTY
PKTMMF001	1 Litre	6
PKTMMF005	5 Litre	4
PKTMMF020	20 Litre	
PKTMMF060	60 Litre	
PKTMMF205	205 Litre	

SPECIFICATIONS & PERFORMANCE LEVEL:

- | | | |
|------------------------|-----------------------------|-----------------------|
| ✓ ATF Type Z-1 | ✓ Hyundai SP-II | ✓ Voith 55.6335 |
| ✓ Allison C-4 | ✓ Kia SP-II | ✓ Volvo 37325 / 37335 |
| ✓ Allison TES-389B | ✓ Mitsubishi Diaqueen SP-II | ✓ ZF TE-ML05L |
| ✓ Chrysler ATF+3 | ✓ M2C166-H | ✓ ZF TE-ML09L |
| ✓ Chrysler MS-7176E | ✓ M2C185-A | ✓ ZF TE-ML21L |
| ✓ Ford MERCON® | ✓ MAN 339 Type V-1 | |
| ✓ GM 6297M | ✓ Mazda M-III | |
| ✓ GM DEXRON® -II | ✓ MB 236.10 / 236.5 / 236.7 | |
| ✓ GM DEXRON® -IIIF / G | | |