

# SAFETY DATA SHEET

# According to Work Health and Safety Regulations 2011 and National Model Code of Practice for the preparation of Safety Data Sheets for Hazardous Chemicals

Version 1.1

Printing date: 18/09/2019

Revision date: 18/09/2019 SDS Record Number: CSSS-TCO-010-116726

1. Identification of the material and supplier

Material name: ZLS 85W/90 Limited Slip Gear Oil

Other means of identification:

Recommended use: Suitable for the requirements on limited slip differential of axle shafts or gearbox

lubrication.

Restrictions on use:

Manufacturer:

Supplier(Manufacturer): SINOPEC LUBRICANT CO.,LTD

Address: No. 6 Anning Zhuang West Road, Haidian District, Beijing, P.R.China

Contact person(E-mail): csc.lube@sinopec.com

 Telephone:
 86-800-810-9886

 Fax:
 86-10-82410856

 Emergency number:
 86-800-810-9886

Australia Supplier(Manufacturer): International Lubricant Distributors Pty. Ltd.

Address: Level 3, 43 Kishorn Road, Applecross, 6153 Australia

Contact person(E-mail): Telephone: -

Fax: +61 8 9381 1788 Emergency number: 1300 558 939

New Zealand Supplier(Manufacturer): Waitomo Lubricants Limited (GST 104255744)

Address: 15 Ellis Street, Frankton, Hamilton, PO Box 5125, Hamilton 3242

**Telephone:** +64 7 847 0829 **Fax:** +64 7 846 0032

**Emergency number:** +64 7 847 0829 (24 Hrs)

New Zealand Supplier(Manufacturer): MTS ENERGY LTD

Address: 44 Northcote Road, North Shore, Auckland 0627, New Zealand

 Telephone:
 +64 9 480 8921

 Fax:
 +64 9 480 8398

**Emergency number:** 0800 399 993 (24 Hrs)

New Zealand Supplier(Manufacturer): Ixom Operations Pty Ltd (Incorporated in Australia)

NZBN: 9429041465226

Address: 166 Totara Street, Mt Maunganui South, New Zealand

Contact person(E-mail): -

**Telephone:** +64 9 368 2700

Material name: ZLS 85W/90 Limited Slip Gear Oil

Version #: 1.1

Printing date: 18-09-2019.

Revision date: 18-09-2019.

SDS Australia&New Zealand

1 / 9



**Fax:** +64 9 368 2710

Emergency number: 0 800 734 607 (ALL HOURS)

## 2. Hazards identification

#### Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

#### **New Zealand:**

Not classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land

#### **GHS** label elements:

**Hazard Pictograms: :**No hazard pictogram is used.

Signal word: No signal word is used.

**Hazard statement:** Not applicable.

**Precautionary statement:** 

Prevention:

Response:

Storage:

Disposal:

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

classification:

# 3. Composition/information on ingredients

Components	CAS No.	Percent	
Highly refined mineral oil	64742-54-7/64742-57-0	85 - 100%	
alkyl sulfur mixtures	-	0-15%	

## 4. First aid measures

**Inhalation:** No specific first aid measures are required. If exposed to excessive levels of material in

the air, move the exposed person to fresh air. Get medical attention if coughing or

respiratory discomfort occurs.

**Skin:** No specific first aid measures are required. As a precaution, remove clothing and shoes if

contaminated. To remove the material from skin, use soap and water. Discard

contaminated clothing and shoes or thoroughly clean before reuse.

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if

worn, and flush eyes with water.

**Ingestion:**No specific first aid measures are required. Do not induce vomiting. As a precaution, get

medical advice.

Symptoms caused by exposure: Not available.

Medical Attention and Special Treatment: Treat symptomatically.

# 5. Fire-fighting measures

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
2 / 9



Extinguishing media which must not be

used for safety reasons:

chemical:

In case of heat, fire and strong oxidants can lead to burning. Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides, phosphate, certain metal oxides and

other decomposition products, in the case of incomplete combustion.

Special protective equipment and precautions for fire fighters:

Specific hazards arising from the

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location.

This product should be prevented from entering drains and watercourses.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid build up of vapour. Ensure sufficient supply of air. Avoid contact with eyes or skin. Contact with water - danger of sliding. Wear appropriate personal protective equipment

and clothing to prevent exposure. Increase ventilation. Evacuate all unprotected

personnel.

Environmental precautions:

If leakage

If leakage occurs, dam up. Prevent surface and ground-water infiltration, as well as ground penetration. Prevent from entering drainage system. If accidental entry into drainage system occurs, inform responsible authorities.

Methods and materials for containment

For large spills: Remove with vacuum truck or pump to storage/salvage vessels.

and cleaning up:

For small spills: Soak up residue with an absorbent such as clay, sand or other suitable

material. Place in non-leaking container and seal tightly for proper disposal.

# 7. Handling and storage

Precautions for safe handling:

Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Electrostatic discharge may be generated during pumping - this may result in fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Conditions for safe storage, including any

incompatibilities:

Do not store in open or unlabeled containers. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Storage regulation

Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940. This product should be stored and used in a well-ventilated area away from naked flames, sparks and other sources of

ignition.

Water.

## 8. Exposure controls/personal protection

Control parameters - exposure

Not available

standards, biological monitoring:

**Exposure Levels** 

Occupational exposure limits:

Australia. National Workplace OELs (Workplace Exposure Standards for Airborne Contaminants, Appendix A)				
Components	Туре	Value	Form	
Not available.	Not available.	Not available.	Not available.	
Australia. OELs. (Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment)				
Components	Туре	Value	Form	
Not available.	Not available.	Not available.	Not available.	

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
3 / 9



No exposure standards have been established for this material, however, the TWA National occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 5 mg/m3, the STEL National occupational Health And Safety Commission (NOHSC) exposure standards for oil mist is 10 mg/m3.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Appropriate engineering controls: Provide sufficient ventilation to keep airborne levels as low as possible. Where vapours or

mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a

local exhaust ventilation system is required.

Personal protective equipment:

**Eye/face protection:** No special eye protection is normally required. Where splashing is possible, wear safety

glasses with side shields as a good safety practice.

**Skin protection:** No special protective clothing is normally required. Where splashing is possible, select

protective clothing depending on operations conducted physical requirements and other

substances in the workplace.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material..If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in

circumstances where air-purifying respirators may not provide adequate protection.

**Hand protection:** Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.

# 9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Form: Oily liquid

Color: Transparent, yellow
Odor: Odorless or slight odor

Odour threshold:

PH:

Not available

Melting point/Freezing point:

Not available

Not available

Soiling point and boiling range:

>230°C (typical)

Flash point: 204 °C (Open Cup)(typical)

Evaporation rate:

Flammability (solid, gas):

Upper/lower flammability or explosive

Not available

Not available

limits:

Vapor pressure: <0.5MPa@40°C

Vapor density: >1(air=1)

 $\begin{array}{ll} \textbf{Density:} & 0.86 \hbox{-} 0.91 \hbox{ kg/l} \ (20 \hbox{°C} \ ) \\ \textbf{Solubility (H$_2$O):} & Insoluble in water. \\ \textbf{Partition coefficient (n-octanol/water):} & > 6 \ (estimated \ value) \\ \end{array}$ 

Auto-ignition temperature: >200°C

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
4 / 9



**Decomposition temperature:** Not available

Viscosity, dynamic: 13.5~<24mm2/s @100°C (212°F)

Specific heat value:

Particle size:

Volatile organic compounds content:

Volatile:

Not available

Not available

Not available

Not available

Release of invisible flammable vapours

Not available

and gases:

**Additional parameters** 

Shape and aspect ratio:

Crystallinity:

Not available

Dustiness:

Not available

Not available

Not available

Not available

Degree of aggregation or agglomeration:

Not available

Not available

Biodurability or biopersistence:

Not available

# 10. Stability and reactivity

Reactivity: Stable under recommended transport or storage conditions.

**Chemical stability:** Stable under normal temperatures and pressures.

**Possibility of hazardous reactions:** Contact with strong oxidants.

Conditions to avoid: Incompatible materials. Avoid extreme temperatures, sun exposure, and the fire source.

**Incompatible materials:** Strong oxidizing agents.

Hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes, nitrogen oxides, phosphate,

certain metal oxides and other decomposition products, in the case of incomplete

combustion.

# 11. Toxicological information

## Toxicological data:

Acute toxicity:

LD50(Oral, Rat): >5g/kg
LD50(Dermal, Rabbit): >5g/kg
LC50(Inhalation, Rat): >10g/m3
Highly refined mineral oil (CAS: 64742-54-7)

 LD50(Oral, Rat):
 > 5000 mg/kg bw

 LD50(Dermal, Rabbit):
 > 2000 mg/kg bw

 LC50(Inhalation, Rat):
 2.18 mg/L air

Highly refined mineral oil (CAS: 64742-57-0)

LD50(Oral, Rat): > 5000 mg/kg bw
LD50(Dermal, Rabbit): > 2000 mg/kg bw
LC50(Inhalation, Rat): 2.18 mg/L air
Skin corrosion/Irritation: No data available.

Serious eye damage/irritation:

Respiratory or skin sensitization:

No data available.

No data available.

No data available.

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand

Revision date: 18-09-2019. 5 / 9



Carcinogenicity:No data available.Reproductive toxicity:No data available.STOT- single exposure:No data available.STOT-repeated exposure:No data available.Aspiration hazard:No data available.

Other information This product has no known adverse effect on human health.

Information on routes of exposure

Symptoms related to exposure

No data available.

No data available.

No data available.

Immediate, delayed and chronic health

No data available.

effects from exposure

# 12. Ecological information

## **Ecotoxicity:**

Acute t	oxicity	Time	Species	Method	Evaluation	Remarks
LC50	N/A	96h	Fish	OECD 203	N/A	N/A
EC50	N/A	48h	Daphnia	OECD 202	N/A	N/A
EC50	N/A	72h	Algae	OECD 201	N/A	N/A

Persistence and degradability: This material is not expected to be readily biodegradable.

**Bioaccumulative potential:** This material contains components with potential to bioaccumulation.

**Mobility in soil:** If into the soil, this material will be adsorbed and not flow.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone

creation potential, endocrine disruption, global warming potential) are expected from this

component.

# 13. Disposal considerations

Safe handling and disposal methods:

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Disposal of any contaminated packaging:

Australia:

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

#### **New Zealand:**

#### **Product Disposal**

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Material name: ZLS 85W/90 Limited Slip Gear Oil Version #: 1.1 Printing date: 18-09-2019.

SDS Australia&New Zealand Revision date: 18-09-2019. SDS Australia&New Zealand



#### **Container Disposal**

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

# 14. Transport information

#### Australia:

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

#### **New Zealand:**

Not classified as Dangerous Goods for transport according to the NZS 5433:2012 Transport of Dangerous Goods on Land.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

#### **U.N. Number**

None Allocated

## **Proper Shipping Name**

None Allocated

**DG Class** 

None Allocated

**Packing Group** 

None Allocated

# 15. Regulatory information

# Safety, health and environmental regulations specific for the product in question

#### Australia:

Not classified as Hazardous according to criteria of National Occupational Health and Safety Commission (NOHSC), Australia. Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

#### **New Zealand:**

Not classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

## Australia HVIC: Listed substance

Not available.

#### **New Zealand Location Test Certificate**

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply	Quantity beyond which controls apply	
	for closed containers	when use occurring in open containers	
Not Applicable	Not Applicable	Not Applicable	

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
7 / 9



#### **New Zealand Approved Handler**

Class of substance

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

Not Applicable	Not Applicable	
Inventory status:		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Not available.
Canada	Domestic Substances List (DSL)	Not available.
Canada	Non-Domestic Substances List (NDSL)	Not available.
China	Inventory of Existing Chemical Substances in China	Not available.
	(IECSC)	
Europe	European Inventory of Existing Commercial Chemical	Not available.
	Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	Not available.
Japan	Inventory of Existing and New Chemical Substances	Not available.
	(ENCS)	
Korea	Existing Chemicals List (ECL)	Not available.
New Zealand	New Zealand Inventory	Not available.
Philippines	Philippine Inventory of Chemicals and Chemical	Not available.
	Substances (PICCS)	

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

Quantities

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information

United States & Puerto Rico

Indication of changes: Version 1.1

Date of preparation or review: 2019.9.18

**Key abbreviations or acronyms** CAS: Chemical Abstracts Service **used:** LC50: Lethal Concentration 50

EC50: Concentration for 50% of maximal effect

LD50: Lethal dose 50%

MAC: maximum allowable concentration, MAC)

PC-TWA: permissible concentration-time weighted average PC-STEL: permissible concentration-short term exposure limit

reference Australia:

Standard for the Uniform Scheduling of Medicines and Poisons.

Approved criteria for classifying hazardous substances [NOHSC: 1008(2004)].

National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:

Not available.

2011(2003)].

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted

carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
Revision date: 18-09-2019. 8 / 9



American Conference of Industrial Hygienists (ACGIH)

## New Zealand:

Workplace Exposure Standards and Biological Exposure Indices

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 0906).

Assigning a hazardous substance to a group standard.

American Conference of IndustriaLHygienists (ACGIH)

Material name: ZLS 85W/90 Limited Slip Gear Oil
Version #: 1.1 Printing date: 18-09-2019. Revision date: 18-09-2019. SDS Australia&New Zealand
9 / 9